


Uni-Plain Tile Vent



Uni-Plain Tile Vent is a discreet ventilating tile suitable for clay and concrete plain tiles that provides 6,000 mm² effective ventilation area.

Product features & benefits

- No batten cutting necessary
- In-line design
- Built in downpipe allows direct ventilation to roof space
- Adaptor available for soil ventilation or mechanical extraction
- Prevents the entry of birds and large insects

Area of application

Suitable for:

- Most concrete and clay plain tiles at a roof pitch at or over 35°
- High or low level roof space ventilation

Material

Polypropylene/PVC

Colours / Product Codes

Antique Red	KG991803
Autumn	KG991823
Brown	KG991836
Brown Gran	KG991802
Hedgerow Brown	KG991818
Red Gran	KG991805
Rustic Red	KG991878
Slate Grey	KG991830
Terracotta	KG991834

Dimensions / Weight (per carton)

300mm long x 330mm wide / 8.5kg

Packaging

10 pcs per carton

Related products

Adaptor & Flexipipe	KG992800
Adaptor only	KG990500
Flexipipe only 100/100mm	KG979900

Installation

The Uni-Plain Tile Vent is positioned in broken bond format, above the course below and the underlay is marked and cut to accommodate the downpipe. The Tile Vent is then positioned adjacent to the next tile, nailed in place and tiling continued as normal.

Regulations and certifications

Complies fully with relevant Building Regulations and British Standards.

PERFORMANCE / TECHNICAL DATA

Provides 6,000 mm² effective vent area

Vent spacing

5mm opening at 1.2m centres
10mm opening at 0.6m centres
25mm opening at 0.24m centres

Airflow resistance

15 litres/sec	30 litres/sec	60 litres/sec
12 Pascals	48 Pascals	191 Pascals

TS-00#13-UK-0214. We assume no liability for typing errors.

Klober Ltd

Unit 6F · East Midlands Distribution Centre · Short Lane · Castle Donington · Derbyshire · DE74 2HA
Tel. +44 (0)1332 813 050 · Fax +44 (0)1332 814 033 · info@klober.co.uk · www.klober.co.uk

KLOBER